



CASTLEGUARD®

HIGH SOLIDS METAL INTERLOCK FINISH



The King of Floor Finishes®


The Castleguard Difference

Castleguard® is specifically formulated to counter the high labor costs associated with hard floor care. **Castleguard** is non-yellowing and non-powdering, which extends your strip cycles and saves many labor hours. **Castleguard** is extremely durable...it resists scuff marks and looks great month after month, even with extremely heavy traffic.

One coat of **Castleguard** equals two coats of most conventional floor finishes. **Castleguard** may be applied to virtually all hard floor surfaces to provide beauty and protection beyond your expectations.

Castleguard's exceptional depth of gloss brings out the hidden beauty of your floors with a "wet look", and its slip-resistant surface promotes safety. See for yourself why supermarkets, retail stores, hospitals, schools and building service contractors call **Castleguard** the "best floor finish in the world."

Available Packaging



FEATURES	ADVANTAGES	BENEFITS
Superior gloss	Presents professional image	Improves worker morale Increases customers' confidence in cleanliness standards
Sealer/Finish combination	Eliminates need for a sealer	Reduces customers' inventory & reduces costly application errors
Self-leveling	Coats are easy to apply	Reduces dollars spent to repair streaked floors Reduces the need for designated floor crews
Non-yellowing	Lengthens time between strip outs	Reduces recoats/cuts labor costs
U.L.® listed for slip resistance	Reduces slip & fall liability	Provides a shiny but safer walking surface
Extremely durable	Doesn't powder when burnished	Reduces recoats/cuts labor costs
Versatile	Can be used with all burnishing programs & on most floor surfaces	Reduces dollars needed for inventory of multiple finishes
Excellent response to burnishing	Improves worker morale for a job well done Consistently shiny floors	Increases customers' confidence in cleanliness standards



CASTLEGUARD®

HIGH SOLIDS METAL INTERLOCK FINISH

DIRECTIONS FOR USE

FLOOR PREPARATION:

1. Strip floor thoroughly using the appropriate Buckeye floor stripper.
2. Rinse floor with clear water, changing rinse water frequently to prevent redepositing of dirt and stripper residue.
3. Allow floor to dry thoroughly before applying **Castleguard**.

APPLICATION:

1. Use a clean mop and clean bucket.
2. Saturate mop with **Castleguard**.
3. Press mop into wringer to remove excess finish. Do not wring mop.
4. Apply **Castleguard**. Best results may be attained by applying medium to full coats.
5. Allow each coat to dry 20 minutes under normal room conditions.

MAINTENANCE:

1. Dust mop floor with an **Aqua Dust™** treated mop.
2. Damp mop as required, using **Buckeye Blue** or **Straight-Up®**.

TECHNICAL SPECIFICATIONS	
pH	7.4 – 7.8
Weight/Gallon	8.58 lbs
Sediment (based on volume)	Less than 0.1%
Film Color	Water Clear
Odor	Bland
Flash Point	None
Heat Stability	Over 30 days @ 125° F
Freeze-Thaw Stability	Pass 3 Cycles
Storage Stability	Excellent*
Slip Resistance	UL Classified
*stored in its original unopened container	



For more information about Castleguard, scan this code.

